

New Product

Quickconnect™ Flexible Sprinkler Droppers

Features

- Max Working Pressure: 175 PSI (12.5 Bar)
- Max Test Pressure: 350 PSI (25 Bar)
- Max Working Temperature: 120° Celsius
- Braided S/S 304
- UL/FM Approved
- Complete with brackets & 1 metre long caring bar
- Complies to AS2118.1 - 2006



Benefits

- No measuring
- No site pipe processing - Cutting, Threading, Welding or Roll Grooving
- No mess & clean up required
- Reduced installation program due to speed of installation

CUSTOMER: _____

Size Range	Price Each (incl. GST)
15nb x 26.8mm 700mm long	
15nb x 26.8mm 1200mm long	
15nb x 26.8mm 1800mm long	
15nb x 26.8mm 2100mm long	

Price includes: 1 x Flexible Dropper Hose, Reducer, Nipple & Reducer Clip, 2 x Ceiling Clips, 1 x 1000mm Caring Bar.

Prices are correct at time of printing & are subject to change at any time without notice. Quickconnect™ is a registered trademark of Fivalco Inc./Aleum CO. Manufactured for OneSteel Building Services by Fivalco.



Contact your nearest branch for further information.

National	1300 553 473	Adelaide	08 8304 7570
Brisbane	07 3420 4099	Melbourne	03 8645 3222
Perth	08 9494 0989	Sydney	02 8788 5810

www.onesteelbuildingservices.com

Copyright 2009. OneSteel Trading Pty Limited ABN 50 007 519 646. August 2009. CS008.

